

Product Features	20G SaltChlor
Salt Level Indicator	YES
Required Salt Level:	3000 to 6000ppm
Salt Level Warning System:	YES
Chlorine Generation Mode:	Below 4000 gal 6000-8000gal 8000-12000gal 12000-15000gal
	Turbo Mode
Digital Display System:	YES
Built in Controller/Timer:	YES
Self Programming:	YES
Self Cleaning:	YES
Plug and Play:	YES
Warranty:	2-Year
Max Production:	20g/h
Cell Units Size:	260x165x123mm
Power Pack Size:	150x120x82mm
Outside Casing	ABS/PMMA
Electrodes:	Titanium with 90g per meter square anode
Electrode Surface Area:	70x150x1 mm (3pcs)
Overload Protection:	YES
Input Voltage (OI & C I):	220V - 240V
Power Consumption:	Max.60w
Output Max Current:	7A
Input Voltage:	18VAC
Input Frequency (OI & C I)	47-63Hz
Minimum Flow Rate:	150 liter per min
Cord Length:	2M
Capacity -Pools /Spas:	15000gal pool
Cell Inlet/Outlet Pipe:	Ø50mm
Total Weight:	4kg per unit
Packing Size:	450x220x145mm
Carton Box:	4pcs per carton 460x450x330mm 17kg per Carton



Control Panel can separated from Cell



Electrolysis Cell

Power Pack

